

## Claims

1. (Currently amended) A computer-implemented method, comprising:  
  
inputting a netlist;  
  
generating symbols and connections formed according to the netlist and ~~a selected wiring harness layout dimension~~ at least in part according to connectivity strength between at least a first symbol and a second symbol; and  
  
generating a wiring harness diagram that comprises along the layout dimension ~~according to the symbols and the connections.~~
2. (Currently amended) The method of claim 1 in which generating the wiring harness diagram ~~further comprises~~ sorting the netlist at least in part according to the connectivity strength of at least one pair of symbols.
3. (Currently amended) A computer-implemented method, comprising ~~The method of claim 1 in which generating the symbols further comprises:~~  
  
inputting a netlist;  
  
generating symbols and connections formed according to the netlist; and  
  
generating a wiring harness diagram, wherein the wiring harness diagram comprises the symbols and the connections, and wherein generating the wiring harness diagram comprises  
  
positioning a pin on a side of a first symbol, the side selected according to (a) a connection between the first symbol and a second symbol, and (b) the layout dimension.

4. (Currently amended) The method of claim [[2]] 1 further comprising:  
  
sequencing symbol placement for the wiring harness diagram such that symbols with predetermined pin positions are placed in the wiring harness diagram layout with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

5. (Currently amended) A computer-implemented method, comprising:  
  
sequencing symbol placement in a wiring harness layout at least in part according to the connectivity strength of at least one pair of symbols; and  
  
generating a wiring harness diagram for at least one bundle according to the wiring harness layout, wherein the bundle comprises a plurality of wires.

6. (Original) The method of claim 5 further comprising:  
  
selecting a side of a first symbol on which to position a pin to increase the directness of connectivity between the first symbol and a second symbol.

7. (Original) The method of claim 5 in which generating a wiring diagram according to the layout further comprises:  
  
selecting sides of the symbols on which to position pins according to a selected layout dimension; and  
  
arranging the pins on the selected sides to increase the directness of connections between the symbols.

8. (Original) The method of claim 5 further comprising:

sequencing symbol placement for the wiring harness diagram such that symbols with predetermined pin positions are placed in the layout with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

9. (Currently amended) A computer-implemented method, comprising:

sequencing symbol placement in a wiring harness layout for at least one bundle comprising signal-carriers, at least in part according to the connectivity strength of at least one pair of symbols; and

selecting a side of a first symbol on which to place a pin to increase the directness of connectivity between the first symbol and a second symbol.

10. (Original) The method of claim 9 in which selecting the side of the first symbol further comprises:

selecting the side according to a selected layout dimension and a position of the second symbol.

11. (Currently amended) The method of claim 9 further comprising:

sequencing symbol placement for the wiring harness layout ~~diagram~~ such that symbols with predefined pin positions are placed in the layout with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

12. (Original) A computer-implemented method, comprising:  
when at least one first pair of symbols of a netlist has been placed in a wiring harness layout, selecting a next pair of symbols to place in the layout comprising at least one symbol of the first pair; and

when there is at least one predefined symbol in the netlist, selecting as the next pair of symbols a pair of symbols having the highest connection strength and comprising a predefined symbol.

13. (Original) The method of claim 12 further comprising:  
selecting for the placement of pins a side of one symbol of the next pair of symbols; and  
arranging the pins along the side to increase the directness of connection between the next pair of symbols.

14. (Currently amended) An article comprising:  
a machine-readable media comprising instructions which, when executed by the processor of a data processing device, result in:  
inputting a netlist;  
generating symbols and connections formed according to the netlist and ~~a selected wiring harness layout dimension~~ at least in part according to connectivity strength between at least a first symbol and a second symbol; and  
generating a wiring harness diagram that comprises ~~along the layout dimension according to~~ the symbols and the connections.

15. (Currently amended) The ~~media~~ article of claim 14 in which the instructions, when executed by the processor to generate the wiring harness diagram, further result in:

sorting the netlist at least in part according to the connectivity strength ~~of at least one pair of symbols.~~

16. (Currently amended) The ~~media~~ article of claim 14 in which the instructions, when executed by the processor to generate the symbols, further result in:

positioning a pin on a side of ~~[[a]]~~ the first symbol, the side selected according to ~~(a)~~ a connection between the first symbol and ~~[[a]]~~ the second symbol, ~~and (b) the layout dimension.~~

17. (Currently amended) The ~~media~~ article of claim 14 in which the instructions, when executed by the processor, further result in:

sequencing symbol placement for the wiring harness diagram such that symbols with predetermined pin positions are placed in the wiring harness diagram ~~layout~~ with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

18. (Currently amended) An article comprising:

a machine-readable media comprising instructions which, when executed by the processor of a data processing device, result in:

sequencing symbol placement in a wiring harness layout at least in part according to the connectivity strength of at least one pair of symbols; and

generating a wiring harness diagram for at least one bundle according to the wiring harness layout, wherein the bundle comprises a plurality of wires.

19. (Currently amended) The ~~media~~ article of claim 18 in which the instructions, when executed by the processor, further result in:

selecting a side of a first symbol on which to position a pin to increase the directness of connectivity between the first symbol and a second symbol.

20. (Currently amended) The ~~media~~ article of claim 18 in which the instructions, when executed by the processor to generate the wiring harness diagram, further result in:

selecting sides of the symbols on which to position pins according to a selected layout dimension.

21. (Currently amended) The ~~media~~ article of claim 18 in which the instructions, when executed by the processor, further result in:

sequencing symbol placement for the wiring harness diagram such that symbols with predetermined pin positions are placed in the layout with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

22. (Currently amended) An article comprising:
- a machine-readable media comprising instructions which, when executed by the processor of a data processing device, result in:
- sequencing symbol placement in a wiring harness layout for at least one bundle comprising signal-carriers, at least in part according to the connectivity strength of at least one pair of symbols; and
- selecting a side of a first symbol on which to place a pin to increase the directness of connectivity between the first symbol and a second symbol.
23. (Currently amended) The ~~media~~ article of claim 18 in which the instructions, when executed by the processor to select the side of the first symbol, further result in:
- selecting the side according to a selected wiring harness layout dimension and a position of the second symbol.
24. (Currently amended) The ~~media~~ article of claim 22 in which the instructions, when executed by the processor, further result in:
- sequencing symbol placement for the wiring harness layout diagram ~~diagram~~ such that symbols with predefined pin positions are placed in the layout with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

25. (Original) An article comprising:  
  
a machine-readable media comprising instructions which, when executed by the processor of a data processing device, result in:  
  
when at least one first pair of symbols of a netlist has been placed in a wiring harness layout, selecting a next pair of symbols to place in the layout comprising at least one symbol of the first pair; and  
  
when there is at least one predefined symbol in the netlist, selecting as the next pair of symbols a pair of symbols having the highest connection strength and comprising a predefined symbol.

26. (Currently amended) The ~~media~~ article of claim 25 in which the instructions, when executed by the processor, further result in:  
  
selecting for the placement of pins a side of one symbol of the next pair of symbols.



27. (Currently amended) An apparatus comprising:

a processor; and

a machine-readable media comprising instructions which, when executed by the processor, result in:

inputting a netlist;

generating symbols and connections formed according to the netlist and ~~a selected wiring harness layout dimension~~ at least in part according to connectivity strength between at least a first symbol and a second symbol; and

generating a wiring harness diagram that comprises ~~along the layout dimension according to the symbols and the connections.~~

28. (Currently amended) The apparatus of claim 27 in which the instructions, when executed by the processor to generate the wiring harness diagram, further result in:

sorting the netlist at least in part according to the connectivity strength ~~of at least one pair of symbols.~~

29. (Currently amended) The apparatus of claim 27 in which the instructions, when executed by the processor to generate the symbols, further result in:

positioning a pin on a side of ~~[[a]]~~ the first symbol, the side selected according to ~~(a)~~ a connection between the first symbol and ~~[[a]]~~ the second symbol, ~~and (b) the layout dimension.~~

30. (Original) The apparatus of claim 27 in which the instructions, when executed by the processor, further result in:

sequencing symbol placement for the wiring harness layout such that symbols with predetermined pin positions are placed in the wiring harness diagram ~~layout~~ with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

31. (Currently amended) An apparatus comprising:  
a processor; and  
a machine-readable media comprising instructions which, when executed by the processor, result in:

sequencing symbol placement in a wiring harness layout at least in part according to the connectivity strength of at least one pair of symbols; and

generating a wiring harness diagram for at least one bundle according to the wiring harness layout, wherein the bundle comprises a plurality of wires.

32. (Original) The apparatus of claim 31 in which the instructions, when executed by the processor, further result in:

selecting a side of a first symbol on which to position a pin to increase the directness of connectivity between the first symbol and a second symbol.

33. (Original) The apparatus of claim 32 in which the instructions, when executed by the processor to generate the wiring harness diagram, result in:

selecting sides of the symbols on which to position pins according to a selected layout dimension; and

arranging the pins on the sides to increase the directness of connection between the symbols.

34. (Original) The apparatus of claim 32 in which the instructions, when executed by the processor, further result in:

sequencing symbol placement for the wiring harness layout such that symbols with predetermined pin positions are placed in the layout with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

35. (Currently amended) An apparatus comprising:

a processor; and

a machine-readable media comprising instructions which, when executed by the processor, result in:

sequencing symbol placement in a wiring harness layout for at least one bundle comprising signal-carriers, at least in part according to the connectivity strength of at least one pair of symbols; and

selecting a side of a first symbol on which to place a pin to increase the directness of connectivity between the first symbol and a second symbol.

36. (Original) The apparatus of claim 35 in which the instructions, when executed by the processor to select the side of the first symbol, result in:

selecting the side according to a selected layout dimension and a position of the second symbol.

37. (Original) The apparatus of claim 35 in which the instructions, when executed by the processor, further result in:

sequencing symbol placement for the layout such that symbols with predefined pin positions are placed in the layout with higher priority than symbols for which the side of the symbol for placing a pin may be selected.

38. (Currently amended) An apparatus comprising:  
a processor; and  
a machine-readable media comprising instructions which, when executed by the processor, result in:

when at least one first pair of symbols of a netlist has been placed in a wiring harness layout, selecting a next pair of symbols to place in the layout comprising at least one symbol of the first pair; and

when there is at least one predefined symbol in the netlist, selecting as the next pair of symbols a pair of symbols having the highest connection strength and comprising a predefined symbol.

39. (Original) The apparatus of claim 38 in which the instructions, when executed by the processor, further result in:

selecting for the placement of pins a side of one symbol of the next pair of symbols.

40. (Original) A carrier wave, comprising:

signals defining component symbols and connections generated according to a netlist and a selected wiring harness layout dimension, the symbols and connections defining a wiring harness diagram along the layout dimension.

41. (Original) A carrier wave, comprising:

signals defining a first and second component symbols, the component symbols comprising pins, the pins positioned on sides of the symbols selected to increase the directness of connectivity between the first symbol and the second symbol.

42. (New) The method of claim 1, wherein the wiring harness diagram corresponds to a wiring harness, the wiring harness comprising at least one bundle of signal-carrying wires.

43. (New) The method of claim 1, wherein the wiring harness diagram is generated along a selected wiring harness layout dimension.

44. (New) The method of claim 42, wherein the signal-carrying wires carry electrical signals.

45. (New) The method of claim 42, wherein the signal-carrying wires carry optical signals.

46. (New) The method of claim 1, wherein the wiring harness diagram represents a wiring harness that establishes connectivity between at least two components.

47. (New) The method of claim 46, wherein at least one component is an electrical component.

48. (New) The method of claim 46, wherein at least one component is an optical component.

49. (New) The method of claim 1, wherein the act of generating a wiring harness diagram comprises resizing at least one symbol.

50. (New) The method of claim 1, wherein the act of generating a wiring harness diagram comprises repositioning at least one symbol.

51. (New) The method of claim 1, wherein the wiring harness diagram further comprises pins, wherein the act of generating the wiring harness diagram comprises arranging the pins to increase directness of connections between at least two symbols, and wherein at least one symbol is resized and at least one symbol is repositioned.

52. (New) The method of claim 7, wherein arranging the pins comprises resizing at least one symbol.

53. (New) The method of claim 7, wherein arranging the pins comprises repositioning at least one symbol.